

Now Stocking Sargent & Greenleaf Security Hardware

8077-108 (8077AD) Combination Padlock

National Stock Numbers:
5340 00 285 6523 (GSA)
5340 01 196 2568 (DLA)
5340 01 217 2009




These high security padlocks are built to conform to stringent federal government specifications, including 30 minute protection against expert manipulation & 10 minute protection against surreptitious entry attack. Field changeable combination with the use of a change key. 125,000 possible combinations. Packaged with change key.

Recommended hasp opening for shackle: 3/8"
Shackle material: Case hardened steel.

1881 (SM181) Sliding Mechanical Deadbolt

**Non-Keyed, full 1" bolt throw,
four optional strikes or less strike**



1881 DEADBOLT

- ◆ May be secured in locked or unlocked position.
- ◆ Hardened steel bolt pins resist sawing and over one ton of thrust.
- ◆ Surface mount design for ease of installation and suitability to a wide range of applications.
- ◆ Accepts any 5/16" diameter shackle padlock such as the S&G 8077-108.
- ◆

National Stock #: 5340-01-210-5589

951C High Security Padlock

This rugged key retaining padlock is built to conform to rigid specifications for indoor and outdoor high security applications. Cast stainless steel body.




- ◆ Body and shackle incorporate exotic barrier materials for maximum resistance against cutting, drilling and sawing.
- ◆ Shrouded shackle offers 5/8" clear opening and provides a high degree of resistance against common wedging attacks.
- ◆ Included: Attached chain & clevis, 1 control key & 3 operating keys.

8497 "The Brute" Electronic Door Deadlatch

**National Stock Numbers:
5340-01-020-5681
6350-00-610-1962**

**Specify In-swing or Out-swing and Strike Number*



- ◆ Surface mounted for ease of installation and suitability for a wide range of applications
- ◆ Inside release knob provides for rapid egress
- ◆ Required voltage: 24VDC, Current: 5.5 to 6.5 amps
- ◆ DC coil resistance: 6 OHMS
- ◆ Min. recommended wire: 18 gauge
- ◆ Strikes available for inswing and outswing doors.
- ◆ Ideal for ATM rooms, cash handling areas, research laboratories, etc.